

EP008012UDSID/EP006012UDSID Timer setting

1. How to set up SKIM to 1 hour from the default 15 minutes.

Note: This procedures have already been done by Yasunaga as the initial setting for Enviroflo EPDS.

No.	Operating procedure	LCD Screen
1	Turn on the power ※Time 3:48 is just an example.	Auto 3:48
2	Display the clock	-
3	Press HOUR + MINUTE for 3 seconds ×2	A11
4	Program No.A11	Auto 3:48
5	Press the SET button	5 20
6	Press the MINUTE button for 3 seconds	5 0
7	Press the MINUTE button to set "0") Press 21 times ※Do not press the HOUR button	Auto 3:48
8	Press the SET button Return to automatic screen	Time "3:48"
9	Press the SET button ※Check the time	Auto 1
10	"OK" ⇒Press the SET button	"ON" 0 : 00
11	Press the SET button	"OFF" 0 : 15
12	Press the SET button	"OFF" 0 : 00
13	Press the MINUTE button Press 45 times to set 1:00 (1 hour)	"OFF" 1 : 00
14	Press the HOUR button once	2
15	Press the SET button	"ON" 0 : 00
16	Press the SET button	"OFF" 0 : 00
17	Press the SET button	Auto
18	Press the SET button	
19	Return to automatic screen	

2. How to confirm the timer (1 hour) setting after setup.

No.	Operating procedure	LCD Screen
1	Turn on the power	Auto 3:55
2	Display the clock	
3	Press the SKIM button to change "Auto" to "Manual"	ON Manual
4	Press HOUR + MINUTE for 3 seconds *See note on right	Auto 3:55
5	Press the SKIM button (Manual → Auto)	Time "3 : 55"
6	Press the SET button	Auto 1
7	Press the SET button	"ON" 0 : 00
8	Press the SET button	"OFF" 1 : 00
9	Press the SET button	2
10	Press the SET button	"ON" 0 : 00
11	Press the SET button	"OFF" 0 : 00
12	Press the SET button	"OFF" 0 : 00
13	Press the SET button	Auto 3:55

<Note>

3. Skipping No.3 procedure will reset the timer setting to default (0:15).

4. Please note that there will be no change to the LCD screen after pressing HOUR + MINUTES for 3 seconds.